

Internet of Things (Iot) Based Smart Health Monitoring System

¹. M. Suresh, ².Ch. Ravisankar

1. Assistant Professor, School of Electronics and Electrical Engineering,
Lovely Professional University, Phagwara, Punjab, India.
2. Assistant Professor, School of Electronics and Electrical Engineering,
Lovely Professional University, Phagwara, Punjab, India.

Abstract:

As increase in gray population day by day which leads to increase in caretaking demands. On the basis of monitoring systems on patient's health are gaining importance currently. This paper depends on checking wellbeing of patients. We have a tendency to strive system as more reliable, energy, eco-friendly system for monitoring patients. It is able to send exact real time parameters of patients. It permits the doctor to observe those health parameters of the patients like temperature, heartbeat in an exceedingly real time. Within a fraction of micro seconds, the patient health is monitored mistreatment totally with different sensors that are associated with the Arduino board. Furthermore, the side project data will be sent to the server with the help of LAN defend hooked up to the Arduino board [1].

Conventionally there are variable techniques to open for the ICU patient's wellbeing checking framework with wired communication technology and transferred to server using wireless techniques. Implanted processor underpins for breaking down the contribution from the patient and every one of the parameters results are kept inside the data.

The system uses IR pulse detector for counting pulse of patient, exploitation sensors are able to solely predict the assorted parameters of both atmosphere and patient, however taking call supported obtained price is critical.

Keywords:

ECG, IOT, IP, IDE, ICSP, ESP8266

Introduction:

Health insurance access and affordability are creating issues all around the globe. There are settled in mixture in light of pay and geography, and the high prices of restorative administrations present

Inestimable challenge for countless people. Enormous amounts of humans are not able to get quality care that they should require. Advancement in PMS provides deeper ways to deal with these challenges. Cardiovascular sickness had demonstrated that in case of the heart attacks heart rate of the patient is important factor [2].

Through this adaptable user-friendly applications, sensors, remedial instruments and remote patient monitoring systems, there are thoroughfare through which performance of human in duties conveyance can be moved forward. These developments in PMS is encouraging in order to prices the transport of thought, and interfacing individual to their human administration suppliers.

Hospitals there were Systems for monitoring of patients health condition continuously. Patient's ECGs, heartbeat...are monitored continuously. What's more, subsequently there might be chance that the illness may assault once more. Patient's wellbeing information will be watched much of the time and sent to server. The time of correspondence (every 60 sec) can be set. Perception have demonstrated that about 20% of patients with a release

analysis of heart failings are again in any event once inside span of 70 days with readmission rates running from 15 to 34% inside 2 – 4 months [3].

Considering these necessities, savvy prosperity checking structures are being structured as an insignificant exertion game plan. Such a structure contains parametric data of patient that stores, process and grant through a close by way, for example, advanced cells, PCs. Such frameworks ought to fulfill exacting wellbeing, security, dependability, long haul ongoing activity prerequisites [4].


Block Diagram:

Fig: Block Diagram of the proposed System

Components required for the System:

- Arduino UNO
- Temperature Sensor
- Heart Beat Sensor
- Wi-Fi Module
- 16×4 LCD

While assembling these components, we can build a device by which the patient's heart beat and body temperature could be continuously monitored and the same data could be uploaded to the internet in real time, by the use of Internet of Things (IOT) [5].

INTERNET OF THINGS (IOT):

Today in our daily life Internet have become one of the prime factors. How individual works play has been changed by the internet. Web helps for certain, reasons like Business, Entertainment, Social Networking, Shopping, E-Commerce trainings, record, Industries, etc. The accompanying new example of Internet can't avoid being Internet of Things (IOT). Observing the reality where a couple of things can recognize, pass on, encode and share information over an Internet Protocol (IP). The communication between the products collect the data at particular intervals, break down and used to start activity, giving a smart system to dissecting, and basic leadership [6].

The Internet of Things is usually considered as interfacing articles. It guaranteed relationship for controlling of those things or remote checking the earth. Nevertheless, these definitions were suggested particularly to part of IOT headway considering the machine to machine intercommunication today. Be that as it may, certified significance of IOT is making an impressive, subtle framework which can be watch, controlled and altered [11].

The thing made reliant on IOT join introduced advancement to improve them to exchange information, with each other or over the Internet and it is assessed that 8 to 60 billion devices will be related by 2020 [12].

Wi-Fi Module (ESP 8266):

As Arduino Uno board don't have the Wi-Fi module embedded in it, we are going to interface the ESP 8266 which is an independent System on chip. It is a minimal effort Wi-Fi microchip having the microcontroller capacity with full TCP/IP stack.

The ESP 8266 can do either encouraging an application or offloading all frameworks administration elements of Wi-Fi. The said module comes with ready to use AT commands (consideration) and in turn used to set the firmware. By which we can easily attach the Arduino board and get about as a lot of WIFI capacity as a Wi-Fi Shield offers. The ESP 8266 module is a practical board with a tremendous, and ever growing community.





Fig: Wi-Fi Module (ESP8266)

ESP8266EX module comes with salient feature like autonomous Wi-Fi; and this feature is used to offload the wi-fi capability requirement of other devices and associated applications. Additionally it boots up using flicker when running an application on it.

It has joined hold memory for improving the introduction of the system in those applications. And remotely accessing to web could be added with the arrangement of essential accessibility (SerialPeripheralInterface /SerialDataInputOutput or InterIntegratedCircuit/ UniversalAsynchronousReceiveTransmittr interface). It is among the most popular Wi-Fi module, which contribute the business; it joins the receiving wire switches, control speaker, channels, control the board modules, which doesn't requires any equipment to be connected externally [7].



Block Diagram of ESP8266

Arduino Microcontroller Board (Arduino UNO):

The Arduino Uno is a microcontroller (μ c.) based development platform board (Hardware) which can be programmed with the help of a programming language (Software) known as Arduino integrated development environment (Arduino IDE).

The Arduino Uno is a μ c. development board where the μ c. IC (Integrated Chip) name is ATmega328P. It has fourteen digital data (of which six can be used as Pulse Width Modulation pins), six basic data sources, a quartz crystal of 16 MHz, a USB connector, a power jack to power up the module, and a reset catch. This board can be directly connected to a working system with the Universal Serial Bus connector for uploading the program as well as to supply the board or it can be powered with an household Alternating Current to Direct Current connector or a battery to start work with it, just after uploading program/code through USB connector.




Fig: Arduino UNO

This board and Arduino Software (IDE) are the Arduino reference variants. There are many types of Arduino boards, of which Uno board is the first of its kind, as well as the reference model especially for the beginners of Arduino programming/projects. [8].

LM35 Temperature Sensor:

The LM 35 is a temperature sensor with high accuracy, which yields voltage, straightly to its relative temperature which is mentioned in Celsius (Centigrade). Also, it has a favorable position over the other straight sensors aligned in ° Kelvin. The LM35 doesn't require any calibration to give regular correct nesses of $\pm 1/4$ °C at room temperature and $\pm 3/4$ °C over a full - 55 to + 150 °C extend of temperature [9] [10].




Fig: Temperature Sensor


Heart Beat Sensor:

It is designed to give heart beat as a digital output when a finger is placed inside the pulse detector. So that this digital output can be transferred to Arduino directly through a digital pin to measure the rate of pulse. The principle of operation of this Heart Beat Sensor is as, light modulation by blood flow through the fingers of each pulse. LM358 IC is a dual low power op-amp contains a bright LED and a light detector. One of those op-amp acts as an amplifier and the other acts as a comparator. Finger becomes slightly opaquer, when blood is pumped through blood vessels by heart, so less amount of photons reach at detector. The detector signal varies with each heart pulse and then converted to electrical pulse [9] [10].



Fig: Heart Beat Sensor

Methodology:



The proposed methodology overcomes by consistent observing of patients, valuable for different patients, database report maintenance and indication to concerned medical officials.

In future we can expand this system by using RFID technology through this technology we can monitor the multiple numbers of patients. They are implemented in the advanced Arduino microcontroller.

The patients in the ICU room can be continuously monitored by sensing the temperature, heart beat rate, gas level with wired. The signals sensed from the patients is millivolt but the sensors volt will be 5v sensors will have the amplifiers the sensed signals is amplified and it won't cause harm to human health. then the signals are send to the Arduino. Using WI-FI module the results will be continuously transmit to internet of thing and the data will be stored directly to the database and if any abnormality the indication will be send to medical officials.

Temperature sensor is utilized to gauge temperature with an electrical yield relative to the temperature (in oC). Heart beat rate screen is an individual checking gadget that enables one to quantify one's pulse continuously or record the pulse for later investigation. It is generally utilized by entertainers of different sorts of physical exercise. The normal resting adult human heart rate ranges from 60–100 bpm.

Conclusion:

The work shown in this paper is product which can able to helpful for medical supervisor for the monitoring of patient's health conditions, who are located in different areas. The Future work of this product is very essential in order to make this system more advance and useful. Thus the enhancement would be by connecting more sensors to this system by which the sensed parameters/values measured could be sent to the internet. Here with the other sensors which could be added to this design, measures various other health parameters and could be beneficial for monitoring the patient in real time. i.e. by connecting all the objects to internet for quick and easy access in real time, and also by establishing a Wi-Fi mesh type network to increase in the communication range.

Reference:

- [1] Pantelopoulos, A., & Bourbakis, N. G. (2009). A survey on wearable sensor-based systems for health monitoring and prognosis. *IEEE Transactions on Systems, Man, and Cybernetics, Part C (Applications and Reviews)*, 40(1), 1-12.
- [2] Rohokale, V. M., Prasad, N. R., & Prasad, R. (2011, February). A cooperative Internet of Things (IoT) for rural healthcare monitoring and control. In *2011 2nd International Conference on Wireless Communication, Vehicular Technology, Information Theory and Aerospace & Electronic Systems Technology (Wireless VITAE)* (pp. 1-6). IEEE.
- [3] Rao, B., Deepa, K., Prasanth, H., Vivek, S., Kumar, S. N., Rajendhiran, A., & Saravana, J. (2012). Indoor navigation system for visually impaired person using gps. *International Journal of Advanced Engineering Technology*, 3(2), 40-43.
- [4] Bazzani, M., Conzon, D., Scalera, A., Spirito, M. A., & Trainito, C. I. (2012, June). Enabling the IoT paradigm in e-health solutions through the VIRTUS middleware. In *2012 IEEE 11th International Conference on Trust, Security and Privacy in Computing and Communications* (pp. 1954-1959). IEEE.
- [5] Klasnja, P., & Pratt, W. (2012). Healthcare in the pocket: mapping the space of mobile-phone health interventions. *Journal of biomedical informatics*, 45(1), 184-198.
- [6] Atzori, L., Iera, A., & Morabito, G. (2010). The internet of things: A survey. *Computer networks*, 54(15), 2787-2805.
- [7] Sultana, Farhana, Maria Yasmin Nila, and Nahida Islam. *Remote Health Monitoring For Critically Ill Patient*. Diss. East West University, 2017.
- [8] *International Journal On Engineering Technology and Sciences – IJETS™* ISSN(P): 2349- 3968, ISSN (O): 2349-3976 Volume II, Issue IX, September – 2015.
- [9] Shelar, M., Singh, J., & Tiwari, M. (2013). Wireless patient health monitoring system. *International Journal of Computer Applications*, 62(6).
- [10] Mansor, H., Shukor, M. H. A., Meskam, S. S., Rusli, N. Q. A. M., & Zamery, N. S. (2013, November). Body temperature measurement for remote health monitoring system. In *2013 IEEE International Conference on Smart Instrumentation, Measurement and Applications (ICSIMA)* (pp. 1-5). IEEE.
- [11] Chaudhury, S., Paul, D., Mukherjee, R., & Haldar, S. (2017, August). Internet of Thing based healthcare monitoring system. In *2017 8th Annual Industrial Automation and Electromechanical Engineering Conference (IEMECON)* (pp. 346-349). IEEE.
- [12] Shaikh, S., & Chitre, V. (2017, May). Healthcare monitoring system using IoT. In *2017 International Conference on Trends in Electronics and Informatics (ICEI)* (pp. 374-377). IEEE.